

HYPERDECK STUDIO HD PRO

TECHNICAL SPECIFICATIONS

Name	HyperDeck Studio HD Pro
SD Video Standards	525i59.94 NTSC, 625i50 PAL
Power Supply	1 x Internal 100 - 240V AC 50/60Hz. 1 x 4 pin XLR 12V DC In for external power supply or battery use.
Physical Installation	1U
Operating Temperature	0° to 40° C (32°to 104° F)
Video Inputs	1
Manufacturer	Blackmagic
SDI Compliance	SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 424M, SMPTE 425M level A and B, SMPTE 2081-1, SMPTE 2081-10, SMPTE 2084 and SMPTE 2108-1.
Power Usage	100 W max.
Weight	2.11kg
Video Outputs	2
Environmental Temperature	-20° to 60° C (-4° to 140° F)
SDI Video Sampling	4:2:2 YUV
Height	44.2mm
SDI Rates	270Mb, 1.5G, 3G, 6G.
Environmental Humidity	0% to 90% non-condensing
SDI Colour Precision	10-bit
Width	482mm
Ethernet	1Gb/s
Depth	236.4mm
SDI Colour Space	REC 601, REC 709, REC 2020. 33 point 3D LUTs can be applied to SDI monitor out.

