

IMAGEPRO 4K

TECHNICAL SPECIFICATIONS

Name	ImagePro 4K
Power Supply	Input power: 100-240 VAC 50/60Hz 125w
Video Inputs	1x HDMI™ 2.0 4K60p 4:4:4 8bit, 4:2:2 10 bit, d 1x DisplayPort 1.2 4K60p 4:4:4 10bit, d and 2x 12G SDI 4K60p 4:2:2 10bit or 4x 3G SDI 1200p@60p 4:2:2 10bit.
Manufacturer	Barco
Weight	6.8kg
Video Outputs	1x HDMI™ 2.0 4K60p 4:4:4 8bit, 4:2:2 10 bit, d 1x DisplayPort 1.2 4K60p 4:4:4 10bit, d and 2x 12G SDI 4K60p 4:2:2 10bit or 4x 3G SDI 1200p@60p 4:2:2 10 bit.
Environmental Temperature	0-40 C (32-104 F)
Height	43.7mm
Environmental Humidity	0-95% non-condensing (non-operating) 0-85% non-condensing (operational)
Width	484.1mm
Depth	404.1mm
Genlock	Analog reference input on BNC connector. Blackburst and Bi-level at SD, and Tri-level at HD Reference output is provided by an internal sync generator capable of Bi-level and Tri-level sync signals
HDCP	HDCP compliance determined by installed cards
Aux Outputs	Up to 6x HD single scaler outputs or 2x 4K60p single scaler outputs supporting independent scaling, sizing, and color correction.
Multiviewer	Video preview on front panel

