

IMAGEPRO II

TECHNICAL SPECIFICATIONS

Name	ImagePro II
Video Inputs	5 fixed inputs (6 with dual output option) - 1x Dual Link DVI-I up to 4K@30p DVI d 1x HD-15 (VGA) - 1x HDMI 1.4 (165 MHz) Excl ImagePRO II Jr - 1x DisplayPort 1.1 Up to 4K@30p (300 MHz max) Excl ImagePRO II Jr - 1x 3G SDI (2x 3G SDI with dual output option)
Manufacturer	Barco
Weight	7.14kg
Video Outputs	6 fixed outputs (7 with dual output option) - 1x Composite NTSC/PAL via BNC - 1x Dual Link DVI-I Up to 4K@30p DVI - 1x HD-15 (VGA) - 1x HDMI 1.4 (165 MHz) Excl ImagePRO II Jr - 1x DisplayPort 1.1 Up to 4K@30p (300MHz max) Excl ImagePRO II Jr - 1x 3G SDI (2x 3G SDI with dual output option)
Environmental Temperature	0-40° C (32-104 F)
Height	44mm
Environmental Humidity	0-95% non-condensing (non-operating) 0-85% non-condensing (operational)
Width	484mm
Depth	470mm
Genlock	Analog reference input/loop on BNC connectors; bi-level and blackburst at SD and tri-level at HD, or locked to any input signal. S3D Sync: input Din connector, output Din connector
HDCP	HDCP compliant
Aux Outputs	N/A
Multiviewer	N/A

