

VIDEOHUB 20X20 12G

TECHNICAL SPECIFICATIONS

Name	Videohub 20x20 12G
SD Video Standards	525i59.94 NTSC, 625i50 PAL
Power Supply	1 x Internal 100 - 240V AC 50/60Hz. IEC power cable required.
Physical Installation	1 rack unit height
Operating Temperature	0° to 40° C (32° to 104° F)
Video Inputs	20
Manufacturer	Blackmagic
SDI Compliance	SMPTE 259M, SMPTE 292M, SMPTE 296M, SMPTE 372M, SMPTE 424M, SMPTE 425M level A and B SMPTE 2081-1, SMPTE 2081-10, SMPTE 2082-10, ITU-R BT.656 and ITU-R BT.601
Power Usage	27.5 W max.
Weight	3.6kg
Video Outputs	20
Environmental Temperature	-20° to 60° C (-4° to 140° F)
SDI Video Sampling	YUV 4:2:2 and RGB 4:4:4
Height	44.2mm
SDI Rates	DVB-ASI, 270Mb, 1.5G, 3G, 6G, 12G.
Environmental Humidity	0% to 90% non-condensing
SDI Colour Precision	10, 12-bit RGB 4:4:4 in all HD and 2K modes, Ultra HD modes up to 2160p30 and 4K modes up to 4Kp30 DCI. 10-bit YUV 4:2:2 in all modes.
Width	482mm
Depth	236.14mm
SDI Colour Space	REC 601, REC 709, REC 2020

